

Duct Air Leakage Tester

G9800 Series - G9802



Standard Accessories

- Duct Air Leakage Tester
- Low flow nozzle
- $\varnothing 6$ Silicone tube (Blue) 4m
- Duct connection hose
- Storage box
- Power cord
- Calibration Certification
- Operation manual

Optional Accessories

- Dust-proof cover
- Static probe

Specifications		Best Accuracy
Air Flow	Range	(Matrix): 36 ~ 640 m ³ /h (Nozzle): 4 ~ 36 m ³ /h
	Accuracy	$\pm 2.5\%$ of the reading ± 0.1 m ³ /h
	Resolution	0.01 m ³ /h
Static Pressure	Range	± 2500 Pa
	Accuracy	1% ± 1 Pa of the reading
	Resolution	0.1 Pa
Temperature	Range	0 ~ 60°C
	Accuracy	± 0.5 °C
	Resolution	0.1°C
Atmospheric Pressure	Range	70 ~ 130k Pa
	Accuracy	$\pm 2\%$ of the reading
	Resolution	0.1k Pa
Power Supply	G9802-0E	100-120V, 1 Phase, 50/60Hz, 16A
	G9802-1E	200-240V, 1 Phase, 50/60Hz, 10A
Weight		Net weight approximately 72 Kg
Dimensions (WxDxH)		54 x 50 x 120 cm
Data Logging		Up to 1000 measurements