

POWER TOOLS

POWER THROUGH EVERY CHALLENGE. BUILT TO PERFORM.

GXT LI-ION

CORDLESS TECHNOLOGY



GAZELLE GXT Cordless Technology delivers reliable power, longer runtime, and greater mobility for professional jobsite use. Designed with high-performance lithium-ion batteries and brushless motor compatibility, the GXT system supports demanding cutting, drilling, fastening, and grinding applications while reducing downtime and improving work efficiency.


GAZELLE
GXT
20V | 5.0AH

12V 10MM BRUSHLESS DRILL DRIVER — GC1220

Power Source	Cordless
Voltage	12V
Battery Capacity	2.0 Ah
Motor Type	Brushless
Max. Torque Gear 1	35 Nm
Max. Torque Gear 2	16 Nm
No Load Speed	0 - 460 / 0 - 1600 RPM
Chuck Capacity	10mm
Max. Screw Diameter	7mm
Torque Settings	20 + 1
Max. Drilling Capacity	
[Wood]	20mm
[Steel]	10mm
Length	170mm
Height	190mm
Weight	0.75kg



Package Includes

- Battery Charger
- 2 x 2.0 Ah Battery Pack
- Driver Bit

20V 13MM BRUSHLESS COMPACT DRILL DRIVER — GC2000i

Power Source	Cordless
Voltage	20V
Battery Capacity	2.0 Ah
Motor Type	Brushless
Max. Torque	60 Nm
No Load Speed	0 - 600 / 0 - 2300 RPM
Tool Holder	All Metal Ratcheting
Chuck Capacity	13mm
Max. Screw Diameter	10mm
Torque Settings	20 + 1
Reverse Function	Yes
Max. Drilling Capacity	
[Wood]	38mm
[Steel]	13mm
Length	152mm
Weight	1.0kg



Package Includes

- Battery Charger
- 2 x 2.0 Ah Battery Pack
- Driver Bit

20V 13MM BRUSHLESS COMPACT HAMMER DRILL — GC2020i

Power Source	Cordless
Voltage	20V
Battery Capacity	2.0 Ah
Motor Type	Brushless
Max. Torque	60 Nm
No Load Speed	0 - 600 / 0 - 2300 RPM
Tool Holder	All Metal Ratcheting
Chuck Capacity	13mm
Max. Screw Diameter	10mm
Impact Rate	0 - 34500 BPM
Torque Setting	20 + 2
Reverse Function	Yes
Max. Drilling Diameter	
[Wood]	38mm
[Steel]	13mm
Length	152mm
Weight	1.1kg



Package Includes

- Battery Charger
- 2 x 2.0 Ah Battery Pack
- Driver Bit

20V 13MM BRUSHLESS HAMMER DRILL 160 Nm

GC2030i

Power Source	Cordless
Voltage	20V
Battery Capacity	5.0 Ah
Motor Type	Brushless
Max. Torque	160 Nm
No Load Speed	
[1st Gear]	0 - 500 RPM
[2nd Gear]	0 - 2100 RPM
Impact Rate	0 - 33600 BPM
Torque Setting	19 + 2
Max. Drilling Diameter	
[Wood]	65mm
[Brick Wall]	16mm
[Steel]	13mm
Weight	1.8kg



Package Includes

- Battery Charger
- 2 x 5.0 Ah Battery Pack
- Auxiliary Handle

20V SDS PLUS BRUSHLESS HAMMER DRILL

GC2050

Power Source	Cordless
Voltage	20V
Battery Capacity	5.0 Ah
Motor Type	Brushless
Tool Holder	SDS Plus
Impact Energy	2.8J
No Load Speed	0 - 1000 RPM
Impact Rate	0 - 4500 BPM
Max. Drilling Capacity	
[Concrete]	24mm
[Metal]	13mm
[Wood]	28mm
Drilling Mode	3-Mode: Rotary Hammer, Hammer Only, Rotation Only
Length	30cm
Weight	2.6kg



Package Includes

- Battery Charger
- 2 x 5.0 Ah Battery Pack
- Chuck Adapter
- Auxiliary Handle
- Depth Gauge
- 13 mm Chuck

20V 6MM BRUSHLESS COMPACT IMPACT DRIVER

GC2032i

Power Source	Cordless
Voltage	20V
Battery Capacity	4.0Ah
Motor Type	Brushless
No Load Speed	0 - 1000 / 0 - 2600 / 0 - 3200 RPM
Impact Rate	0 - 700 / 0 - 3600 / 0 - 4300 IPM
Torque Settings	0 - 28 / 0 - 170 / 0 - 208 Nm
Tool Holder	6.35 mm Hex
Bolt Size	M5 - M16
Variable Speed	Yes
Reverse Function	Yes
Length	107mm
Weight	1.0kg



Package Includes

- Battery Charger
- 2 x 4.0 Ah Battery Pack

20V 1/2 IN. BRUSHLESS IMPACT WRENCH

GC2034

Power Source	Cordless
Voltage	20V
Battery Capacity	5.0 Ah
Motor Type	Brushless
Max Torque	488 Nm
Breakaway Torque	682 Nm
No Load Speed	0 - 1800 / 0 - 2100 / 0 - 2400 RPM
Impact Rate	0 - 2600 / 0 - 3000 / 0 - 3500 IPM
Torque Settings	0 - 350 / 0 - 400 / 0 - 488 Nm
Standard Bolt Size	M12 - M20
Tool Holder	1/2 in. Square
Variable Speed	Yes
Reverse Function	Yes
Length	160 mm
Height	250 mm
Weight	1.4 kg



Package Includes

- Battery Charger
- 2 x 5.0 Ah Battery Pack
- Socket

20V 1/2 IN. BRUSHLESS TORQUE WRENCH

GC2036

Power Source	Cordless
Voltage	20V
Battery Capacity	5.0 Ah
Motor Type	Brushless
Max Torque	698 Nm
Breakaway Torque	910 Nm
No Load Speed	0 - 500 / 0 - 1200 / 0 - 1900 / 0- 2200 RPM
Impacts Per Minute	0 - 1000 / 0 - 1700 / 0 - 2400 / 0 - 2700 IPM
Torque Settings	0 - 300 / 0 - 400 / 0 - 500 / 0 - 698 Nm
Tool Holder	1/2 in Square
Standard Bolt Size	M10 - M24
Variable Speed	Yes
Reverse Function	Yes
Length	180 mm
Height	270 mm
Weight	1.9 kg



Package Includes

- Battery Charger
- 2 x 5.0 Ah Battery Pack



20V 125MM BRUSHLESS ANGLE GRINDER — GC2038

Power Source	Cordless
Voltage	20V
Battery Capacity	5.0 Ah
Motor Type	Brushless
Disc Diameter	125mm
Bore Size	16mm
Switch Type	Slide Switch
No Load Speed	9000 RPM
Spindle Thread	M14
Length	360mm
Weight	1.9kg



Package Includes

- Battery Charger
- 2 x 5.0 Ah Battery Pack
- Auxiliary Handle
- Wrench

20V 7 IN. BRUSHLESS CIRCULAR SAW (BARE) — GC2046B

Power Source	Cordless
Voltage	20V
Motor Type	Brushless
No Load Speed	0 - 5000 RPM
Blade Diameter	185mm
Blade Bore	20mm
Max Cutting Angle	45°
Max. Depth of Cut	
[90°]	65mm
[45°]	45mm
Batteries Included	No
Weight	3.5kg



Package Includes

- Hex Wrench
- Fixing Plate

20V BRUSHLESS COMPACT BLOWER — GC2044

Power Source	Cordless
Voltage	20V
Battery Capacity	4.0 Ah
Motor Type	Brushless
Blowing and Suction	Yes
No Load Speed	0 - 11000 / 0 - 15000 / 0 - 18000 RPM
Air Flow	0 - 67 / 0 - 92 / 0 - 110 CFM
Weight	1.3kg



Package Includes

- Battery Charger
- 1 x 4.0 Ah Battery Pack
- Blowpipe
- Dust Bag
- Dust Extraction Connector

GAZELLE®

BRUSHLESS

REBAR TYING



Tying Speed
0.5sec

Max Rebar Size
44mm

Ties per Charge
4000



ADJUSTABLE TIGHTNESS



CONSISTENT PRODUCTIVITY

BRUSHLESS REBAR CUTTER — GC2070

Power Source	Cordless
Voltage	18V
Battery Capacity	5.0 Ah
Max Cutting Capacity	5 - 20mm
Head Rotation Angle	360º
Cutting Speed	3 - 5secs
Dimension w/ Battery & Handle	408 x 172 x 360mm
Weight w/ Battery	6.8kg



Package Includes

• Battery Charger • 2 x 5 .0 Ah Battery Pack

Sold Separately: GC2070-BL - Rebar Cutting Machine Blade

BRUSHLESS REBAR TYING MACHINE — GC2075

Power Source	Cordless
Voltage	18V
Battery Capacity	5.0 Ah
Rebar Size	12 - 44mm
Tying Speed	0.5sec
Wraps per Tie	1 Wrap
Ties per Charge	Over 4000 ties
Dimension	320 x 97 x 335mm
Weight w/ Battery	2.9kg
Wire Coil	
Length	37 ± 1m
Diameter	1.3mm
Ties per Coil	
D10 x D10	325 Ties
D12 x D12	295 Ties
D16 x D16	255 Ties
D20 x D20	225 Ties
D25 x D12 x D12	225 Ties



Package Includes

• Battery Charger • 2 x 5 .0 Ah Battery Pack

Sold Separately: GC2075-RL - Rebar Tying Reel 1.3MM

REBAR FLUSH CUTTER — GC2078

Power Source	Cordless
Voltage	18V
Battery Capacity	5.0 Ah
Max Cutting Capacity	30mm
No Load Speed	2000 RPM
Blade Diameter	127mm
Dimension	475 x 160 x 107mm
Weight w/ Battery	3.8kg



Package Includes

• Battery Charger • 2 x 5 .0 Ah Battery Pack

Sold Separately: GC2070-BL - Rebar Cutting Machine Blade

20V

GXT LI-ION



GC1020
20V 2.0AH LI-ION BATTERY

GC1040
20V 4.0AH LI-ION BATTERY

GC1050
20V 5.0AH LI-ION BATTERY

MULTI VOLTAGE CHARGER GC1000



Voltage	110 - 240V
Frequency	50-60Hz

20V 2.0AH LI-ION BATTERY GC1020



Battery Voltage	20V
Battery Capacity	2.0 Ah

20V 4.0AH LI-ION BATTERY GC1040



Battery Voltage	20V
Battery Capacity	4.0 Ah

20V 5.0AH LI-ION BATTERY GC1050



Battery Voltage	20V
Battery Capacity	5.0 Ah

10MM ROTARY DRILL, 460W

GD1010

Power Source	Corded
Voltage	220V
Power Input	460W
No Load Speed	3200 RPM
Chuck Capacity	10 mm
Max. Drilling Capacity	
[Steel]	10 mm
[Wood]	25 mm
Weight	1.3 kg



Package Includes

- Carbon Brush

13MM IMPACT DRILL, 710W

GD1320

Power Source	Corded
Voltage	220V
Power Input	710W
No Load Speed	3200 RPM
Impact	0 - 4500 BPM
Chuck Capacity	13mm
Max. Drilling Capacity	
[Wood]	30mm
[Metal]	13mm
[Brick Wall]	16mm
Length	270mm
Weight	2.0kg



Package Includes

- Auxiliary Handle
- Depth Gauge
- Chuck Wrench
- Carbon Brush

26MM SDS-PLUS ROTARY HAMMER, 800W

GH2210

Power Source	Corded
Voltage	220V
Bit Type	SDS Plus
Power Input	800W
Operation Modes	Hammering / Rotation / Hammering with Rotation
Max. Impact Energy	3.0J
No Load Speed	0 - 1200 RPM
Blows Per Minute	0 - 4000 BPM
Max. Drilling Capacity	
[Concrete]	26mm
[Steel]	13mm
[Wood]	30mm
Weight	2.93kg



Package Includes

- Auxiliary Handle
- Depth Gauge
- Carbon Brush

28MM SDS-PLUS ROTARY HAMMER, 850W — GH2810

Power Source	Corded
Rated Voltage	AC 220 - 240V~ / 110V
Frequency	50/60Hz
Power Input	850W
No Load Speed	0 - 1200 RPM
Impact Rate	0 - 5300 BPM
Tool Holder Type	SDS Plus
Impact Energy	3.2J
Max. Drilling Capacity	
[Concrete]	28mm
[Steel]	13mm
[Wood]	32mm
Optimum Range Concrete Hammer Drill Bit	8 - 16mm
Counterbalance Vibration Control	Yes
Weight	2.9kg



Package Includes

- Auxiliary Handle
- Staff Gauge
- Grease

42MM SDS-MAX ROTARY HAMMER, 1200W — GH2860

Power Source	Corded
Rated Voltage	220V - 240V~
Frequency	50/60Hz
Power Input	1200W
No Load Speed	235 - 514 RPM
Impact Rate	1350 - 2950 BPM
Impact Energy	2 - 10J
Tool Holder Type	SDS-Max
Max. Drilling Capacity	
[Drill Bit]	ø42mm
[Core Bit]	ø90mm
Optimum Drilling Diameter in Concrete	ø18 - ø30mm
Chisel Positioning	12 Step
Weight w/o Cord	6.5 kg



Package Includes

- Carbon Brush
- Auxiliary Handle
- Staff Gauge

45MM SDS-MAX ROTARY HAMMER, 1500W — GH2870

Power Source	Corded
Rated Voltage	220V - 240V~ / 110V
Frequency	50/60Hz
Power Input	1500W
No Load Speed	150 - 305 RPM
Impact Rate	1380 - 2760 BPM
Impact Energy	2 - 15J
Tool Holder Type	SDS-Max
Max. Drilling Capacity	
[Drill Bit]	ø52mm
[Core Bit]	ø125mm
Optimum Drilling Diameter in Concrete	ø25 - ø45mm
Protection Class	II
Weight w/ Cord	8.9kg



Package Includes

- Carbon Brush
- Auxiliary Handle

5KG DEMOLITION HAMMER, 1200W

GH2950

Power Source	Corded
Rated Voltage	AC 230V / 110V
Frequency	50/60Hz
Power Input	1200W
Impact Rate	3100 BPM
Impact Energy	8J
Chisel Positioning	12 Step
Weight (Without Cord)	5.6kg
Chiselling ah,Cheq	13.125 m/s^2, k=1.5m/s^2
Sound Pressure Level L_{pA}	85.68 dB(A)
Sound power level L_{WA}	99.68 dB(A)
Uncertainty K	3 dB(A)
Guaranteed sound power level (according to 2000/14/EC) "Chiselling mode":	105 dB(A)



Package Includes

- Carbon Brush
- Bull Point Chisel
- Grease
- Flat Chisel

10KG SDS-MAX DEMOLITION HAMMER, 1500W

GH2970

Power Source	Corded
Rated Voltage	AC 220V - 240V / 110V
Frequency	50/60Hz
Power Input	1500W
Impact Rate	1000-1900 BPM
Impact Energy	6-17J
Chisel Positions	12 Step
Tool Holder	SDS-Max
Protection Class	II
Weight	10.5kg
Chiseling ah,Cheq	19.93 m/s2, k=1.5m/s2
Sound pressure level L_{pA}	92.19dB(A)
Sound power level L_{WA}	103.19dB(A)
Uncertainty K	3 dB(A)
Guaranteed Sound Power Level (According to 2000/14/EC) "Chiseling mode":	105 dB(A)



Package Includes

- Carbon Brush
- Bull Point Chisel
- Grease
- Flat Chisel

11KG SDS-MAX DEMOLITION HAMMER, 1650W

GH2990

Power Source	Corded
Rated Voltage	AC 220V - 240V / 110V
Frequency	50/60Hz
Power Input	1650W
Impact Rate	1050-2100 BPM
Impact Energy	5-19J
Chisel Positions	12 Step
Tool Holder	SDS-Max
Weight	12.8kg



Package Includes

- Carbon Brush
- Bull Point Chisel
- Grease
- Flat Chisel

16KG HEX DEMOLITION HAMMER, 1600W

GH3040

Power Source	Corded
Rated Voltage	AC 220V - 240V
Frequency	50/60Hz
Power Input	1600W
Impact Rate	1450BPM
Impact Energy	35J
Tool Holder	30mm HEX
Weight	17.0kg
Protection Class	II
Chiselling ah,Cheq	9.529 m/s^2, k=1.5m/s^2
Sound pressure level L_{pA}	83.98dB(A)
Sound power level L_{WA}	103.66 dB(A)
Uncertainty K	3 dB(A)
Guaranteed sound power level (According to 2000/14/EC) "Chiselling mode":	105 dB(A)



Package Includes

- Carbon Brush
- Bull Point Chisel
- Grease
- Flat Chisel

28KG HEX DEMOLITION HAMMER, 2000W

GH3070

Power Source	Corded
Voltage	AC 220V - 240V
Frequency	50/60Hz 15A
Power Input	2000W
Impact Rate	1000/min
Impact Energy	62J
Tool Holder	28mm Hex
Weight	29.1kg



Package Includes

- Carbon Brush
- Bull Point Chisel
- Grease
- Flat Chisel
- Trolley



GC2050
20V SDS Plus Brushless Hammer Drill
See page 04

4 IN. ANGLE GRINDER WITH PADDLE SWITCH, 800W

GM4010

Power Source	Corded
Voltage	220V
Power Input	800W
Disc Diameter	100mm
Bore Size	16mm
Switch Type	Paddle Switch
No Load Speed	0 - 13000 RPM
Spindle Thread	M10
Length	270mm
Weight	1.5kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

4 1/2 IN. ANGLE GRINDER WITH SLIDE SWITCH, 950W

GM4510i

Power Source	Corded
Voltage	220V
Power Input	950W
Disc Diameter	115mm
Bore Size	22mm
Switch Type	Slide Switch
No Load Speed	0 - 11800 RPM
Spindle Thread	M14
Length	260mm
Weight	1.8kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

4 1/2 IN. ANGLE GRINDER WITH PADDLE SWITCH, 800W

GM4520

Power Source	Corded
Voltage	220V / 110V
Power Input	800W
Disc Diameter	115mm
Bore Size	22mm
Switch Type	Paddle Switch
No Load Speed	0 - 11800 RPM
Spindle Thread	M14
Length	270mm
Weight	1.5kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

4.5IN ANGLE GRINDER WITH PADDLE SWITCH, 1100W — GM4525

Power Source	Corded
Voltage	220V
Power Input	1100W
Disc Diameter	115mm
Bore Size	22mm
Switch Type	Paddle Switch
No Load Speed	0 - 11800 RPM
Spindle Thread	M14
Weight	2.0kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

5 IN. ANGLE GRINDER WITH PADDLE SWITCH, 1500W — GM4550

Power Source	Corded
Voltage	220V
Power Input	1500W
Disc Diameter	115 / 125mm
Bore Size	22mm
Switch Type	Paddle Switch
No Load Speed	0 - 11800 RPM
Spindle Thread	M14
Electronic Constant Speed Control	Yes
Length	380mm
Weight	2.3kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

7 IN. ANGLE GRINDER WITH PADDLE SWITCH, 2200W — GM4570

Power Source	Corded
Voltage	220V
Power Input	2200W
Disc Diameter	180mm
Bore Size	22mm
Switch Type	Paddle Switch
No Load Speed	8300 RPM
Spindle Thread	M14
Length	480mm
Weight	5.0kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

9 IN. ANGLE GRINDER WITH PADDLE SWITCH, 2200W

GM4590

Power Source	Corded
Voltage	220V
Power Input	2200W
Disc Diameter	230mm
Bore Size	22mm
Switch Type	Paddle Switch
No Load Speed	6600 RPM
Spindle Thread	M14
Length	480mm
Weight	5.0kg



Package Includes

- Auxiliary Handle
- Wrench
- Carbon Brush
- Wheel Guard

6MM DIE GRINDER WITH SLIDE SWITCH, 550W

GM4580

Power Source	Corded
Voltage	220V
Power Input	550W
Max. Grinding Wheel Size	25mm
Collet Size	6mm
Switch Type	Slide Switch
No Load Speed	9000 - 26700 RPM
Length	370mm
Weight	1.6kg



Package Includes

- Wrench
- Collet
- Barrel Guard
- Carbon Brush

14 IN. HIGH POWER CHOPSAW, 2000W

GM4535

Power Source	Corded
Voltage	220V
Power Input	2000W
Blade Diameter	355mm
Bore Size	25.4mm
No Load Speed	0 - 3800 RPM
Cutting Capacity 0 to 45o mitre	
[Round Bar]	65mm
[Pipe]	120mm
[Profiled Bar]	120 x 130mm
Weight	16.0kg



Package Includes

- Hex Wrench
- Carbon Brush

7 IN. CIRCULAR SAW, 1500W

GW7030

Power Source	Corded
Voltage	220V
Power Input	1500W
Blade Diameter	185mm
Blade Bore	25.4mm
No Load Speed	0 - 5300 RPM
Max. Cutting Capacity 90°	64mm
Bevel Capacity	45°
Weight	4.1kg



Package Includes

- Hex Wrench
- Blade
- Fixing Plate
- Carbon Brush

9 IN. CIRCULAR SAW, 2000W

GW7040

Power Source	Corded
Voltage	220V
Power Input	2000W
Blade Diameter	235mm
Blade Bore	25.4mm
No Load Speed	0 - 4100 RPM
Max. Cutting Angle	50°
Bevel Capacity	45°
Max. Depth of Cut	
[90°]	85mm
[45°]	60mm
Weight	6.5kg



Package Includes

- Hex Wrench
- Blade
- Fixing Plate
- Carbon Brush

110MM ELECTRIC TILE CUTTER, 1400W

GT1400

Power Source	Corded
Voltage	220V
Power Input	1400W
Blade Diameter	110mm
Bore SIze	20mm
No Load Speed	0 - 13850 RPM
Max. Cutting Capacity	30mm
Weight	2.9kg



Package Includes

- Socket Wrench
- Wrench
- Carbon Brush

12 IN. DUAL-BEVEL SLIDING COMPOUND MITER SAW, 1650W

GW7000

Power Source	Corded
Voltage	AC 220V - 240V
Frequency	50Hz
Power Input	1650W
No Load Speed	3400 RPM
Saw Blade	⌀305mm x ⌀25.4mm x 60T
Maximum Miter (Left/Right)	51°/ 60°
Maximum Bevel(Left/Right)	47°/ 47°
Weight	25.5kg
Sound Pressure level L_{pA}	93 dB(A)
Uncertainty K_{pA}	3 dB(A)
Sound Pressure level L_{WA}	106 dB(A)
Uncertainty K_{WA}	3 dB(A)



Package Includes

- Carbon Brush
- Base Handle
- Kerf Board
- Platen Assembly
- Dust Bag

JIGSAW, 580W

GW7050

Power Source	Corded
Voltage	220V
Power Input	580W
No Load Stroke Rate	0 - 500 / 0 - 3100 SPM
Bevel Capacity	45º (Left / Right)
Max. Cutting Capacity	
[Wood]	85mm
[Steel]	10mm
Variable Speed	Yes
Length	250mm
Weight	2.7kg



Package Includes

- Saw Blade
- Plastic Base
- Hex Wrench
- Carbon Brush
- Blade Gauge

RECIPROCATING SAW, 1300W

GM4560

Power Source	Corded
Voltage	220V
Power Input	1300W
No Load Stroke Rate	2900 SPM
Stroke Length	30mm
Max. Cutting Capacity	
[Wood]	255mm
[Steel Sections & Pipes]	130mm
Weight	3.8kg



Package Includes

- Saw Blade
- Carbon Brush

680W VARIABLE SPEED BLOWER

GB8000

Power Source	Corded
Voltage	220V
Power Input	680W
Speed	0 - 8300 / 0 - 16300 RPM
Air Flow	0 - 56.5 / 0 - 113 CFM
Blowing and Suction	Yes
Length	460mm
Height	170mm
Weight	1.8kg



Package Includes

- Blowpipe Assembly
- Dust Bag Assembly
- Carbon Brush

2000W VARIABLE SPEED HEATGUN

GH2000

Power Source	Corded
Voltage	220V
Power Input	2000W
Temperature Range	50 - 480 / 50 - 600 °C
Air Flow	210 - 250 / 340 - 450 l/min
Weight	0.80kg



Package Includes

- Flat Wind Tube
- Round Wind Tube



GC2046B
20V 7 in. Brushless Circular Saw
See page 06

240W 1/4 IN. SHEET SANDER

GW7010

Power Source	Corded
Voltage	220V
Power Input	240W
Orbits Rate	14000 OPM
Paper Size	100 x 110mm
Dust Sealed Switch	Yes
Weight	1.2kg



Package Includes

- Carbon Brush

300W 5 IN. RANDOM ORBITAL SANDER

GW7020

Power Source	Corded
Voltage	220V
Power Input	300W
Variable Speed	Yes
Orbits Rate	4000 - 12000 OPM
Disc Diameter	125mm
Dust Sealed Switch	Yes
Weight	1.4kg



Package Includes

- Dust Bag
- Carbon Brush

320W 1/2 SHEET FINISHING SANDER

GW7025

Power Source	Corded
Voltage	220V
Power Input	320W
No Load Speed	0 - 14000 RPM
Planing Size	93 x 185mm
Weight	1.63kg



Package Includes

- Carbon Brush

7 IN. VARIABLE SPEED POLISHER, 1400W

GM4518

Power Source	Corded
Voltage	220V
Power Rate	1400W
Pad Size	180mm
Bore Size	22mm
Switch Type	Trigger Switch
No Load Speed	690 - 3800 RPM
Spindle Thread	M14
Length	370mm
Weight	3.4kg



Package Includes

- Wool Bonnet
- Hex Wrench
- Carbon Brush

1/4 IN. ELECTRIC TRIMMER, 550W

GW7055

Power Source	Corded
Voltage	220V
Power Input	550W
No Load Speed	0 - 30000 RPM
Max Milling Cutter Diameter	6.35mm
Weight	1.6kg



Package Includes

- Straight Guide
- Trimmer Guide Assembly
- Template Guide
- Wrench
- Carbon Brush

ROUTER, 1850W

GW7060

Power Source	Corded
Voltage	220V
Power Input	1850W
No Load Speed	0 - 22000 RPM
Max Milling Cutter Diameter	12.7mm
Weight	6.0kg



Package Includes

- Straight Guide
- Template Guide
- Trimmer Guide Assembly
- Wrench
- Carbon Brush
- Retainer Base Assembly
- Collet (6.35 & 9.52 mm)

24L OIL-FREE AIR COMPRESSOR, 750W

GW7070

Power Input	750W
Working Pressure	8 Bar
Rated Speed	0 - 1400 min
Capacity	24 L
Displacement	≥ 45 L/min
Oil Free	Yes
Weight	20.0kg



Package Includes

- Muffler
- Foot Pad
- 2 x Wheels

50L OIL-FREE AIR COMPRESSOR, 1500W

GW7075

Power Input	1500W
Working Pressure	8 Bar
Rated Speed	0 - 1400 min
Capacity	50 L
Displacement	≥ 95 L/min
Oil Free	Yes
Weight	36.8kg



Package Includes

- Muffler
- 4 x Wheels



LASER DISTANCE METER, 60M

G9503-II

Range	60m
Measurement Accuracy	±0.2mm
Unit of Measurement	m, ft, in
Surface Unit	m², ft², in²
Laser Type	620~690nm
Laser Class	Class II, <1 mW
Single Measurement Time	0.25 s
Work Temperature	0° C +40°C
Storage Temperature	-20° C +65° C
Battery Type	Alkaline AAA, 3x1.5V
Measurement per Battery	Approx. 5,000
Weight (w/o Battery)	Approx. 85g
Dimensions (LxWxH)	115 x 50 x 25mm



Package Includes

- Operating Manual
- Soft Carry Case
- Battery

LASER DISTANCE METER, 120M

G9504-II

Range	120m
Measurement Accuracy	±0.2mm
Unit of Measurement	m, ft, in
Surface Unit	m², ft², in²
Laser Type	620~690nm
Laser Class	Class II, <1 mW
Single Measurement Time	0.25 s
Work Temperature	0° C +40°C
Storage Temperature	-20° C +65° C
Battery Type	Alkaline AAA, 3x1.5V
Measurement per Battery	Approx. 5,000
Weight (w/o Battery)	Approx. 85g
Dimensions (LxWxH)	115 x 50 x 25mm



Package Includes

- Operating Manual
- Soft Carry Case
- Battery

2-LINE GREEN LASER LEVEL, 30M

G9505-II

Laser Type	Green Laser
Laser Lines	2 lines / vertical / horizontal
Laser Class	2
Laser Wavelength	505-503nm
H/V Accuracy	±2mm/10m
Operating Distance	30m
Self-Leveling Range	4°±1°
IP Rating	IP54
Power Source	1.5V battery x 4
Operating time	~8 hours normal mode ~10 hours pulse mode ~30 hours power saver mode
Operating Temperature	-10°C to 50°C
Mount Size	1/4-20 mounting thread
Storage Temperature	-25°C to 75°C



Package Includes

- Operation Manual
- Target Plate
- Magnetic Mounting Bracket
- Eye Glasses
- Hard Carry Case
- Batteries

12-LINE GREEN LASER LEVEL, 60M

G9506-II

Laser Type	Green LD
Laser Lines	3D 12 lines
Laser Class	2
Laser Wavelength	520nm
H/V Accuracy	±3mm/10m
Operating Distance	60m
Self-Leveling Range	±3°
Self-Leveling Time	<3s
IP Rating	IP54
Remote Control	√
Outdoor Pulse Mode	√
Power Source	3.7V Li-ion battery 5200mAh
Operating Hours	>6h
Product Net Weight	694g
Product Size	138 x 89 x 147mm



Package Includes

- Operation Manual
- Target Plate
- Magnetic Mounting Bracket
- Eye Glasses
- USB Cable
- Adapter
- Hard Carry Case
- 2 x Batteries

16-LINE GREEN LASER LEVEL, 30M

G9507

Laser Type	Green LD
Laser Lines	16 Lines
Laser Class	2
Laser Wavelength	510-520nm
H/V Accuracy	±3mm/10m
Operating Distance	30m
Distance from Wall	13mm
Distance from Ground	13mm
Self-Leveling Range	4°(±1°)
Self-Leveling Time	≤3s
Leveling	Automatic/Manual
IP Rating	IP54
Power Source	12V-2600mAh Lithium battery pack
Battery Charging Time	Approx. 4 hours
Reference Operating Hours (default test with all lasers on)	First gear approx. 7 hours Second gear approx. 12 hours Third gear approx. 18 hours
Operating Temperature	-20°C~+40°C
Storage Temperature	-20°C~+60°C
Mount Size	1/4" - 20 mounting thread
Product Size	100 x 77.3 x 112mm
Net weight (weight Li-ion battery)	0.48kg



Package Includes

- Operation Manual
- Target Plate
- Bracket with Back Clip
- Eye Glasses
- USB Cable
- Adapter
- Remote Control
- Hard Carry Case
- 2 x Batteries

UNIVERSAL TRIPOD

G9903

Adjustable Height	600 - 1500 mm
Four-Section Lever-Lock Legs	√
Universal Interface	5/8" screw with 1/4" adapter
Reinforcement Support Design	√



Package Includes

- Soft Carrying Bag
- Adapter