

Coating Thickness Gauge

G9400 Series - G9420



Standard Accessories

- Operating Manual
- Non-ferrous Substrate
- Standard Coating Thickness Sheet (51 m - 1008 m)
- Hard Carry Case
- Ferrous Substrate
- 2 x Sensor Cover
- USB Cable
- Hand Rope
- PC Software CD

Function	Range	Thickness	Resolution	Accuracy
Ferrous and Non-ferrous	0~1250μm	0~99.9μm	0.1μm	±(1+3%)μm
		100~1250μm	1μm	
	0~49.2mil	0~4.99mil	0.01mil	±(0.04+3%)mil
		5.0~49.2mil	0.1mil	
Features				
Minimum Convex Radius of Curvature			5mm	
Minimum Concave Radius of Curvature			50mm	
Minimum Measured Area Diameter			20mm	
Minimum Substrate Thickness			0.5mm	
Display Screen			2in TFT LCD with 320*240 Screen	
Auto Rotatable Screen			Yes	
Unit Conversion			μm / mil	
Alarm Indication			Yes	
Audio Indication			Yes	
Limit Setting			Yes	
Measurement Method			Single / Continues	
Statistical Measurement			Max / Min / Average	
Automatic Identification			Yes	
USB Communication			Yes	
Data Storage			500 Groups	
Backlight Brightness			5 Levels	
Auto Power Off			5 minutes	
Low Battery Indication			2.2V±0.2V Low Battery Indication	