

## Duct Air Leakage Tester

G9800 Series - G9802



### Standard Accessories

- Duct Air Leakage Tester
- Low flow nozzle
- ø6 Silicone tube (Blue) 4m
- Duct connection hose
- Storage box
- Power cord
- Calibration Certification
- Operation manual

### Optional Accessories

- Dust-proof cover
- Static probe

Specifications		Best Accuracy
Air Flow	Range	Large Nozzle: 41 ~ 483 CFM Small Nozzle: 2.4 ~ 41 CFM
	Accuracy	± (2.5% of reading +0.06 CFM)
	Resolution	0.01 CFM
Static Pressure	Range	± 10 in. wg.
	Accuracy	± (1% of reading +0.004 in. wg.)
	Resolution	0.001 in. wg.
Temperature	Range	32°F ~ 140°F
	Accuracy	±1°F
	Resolution	0.1°F
Atmospheric Pressure	Range	20.6 ~ 38.3 in. Hg.
	Accuracy	± 2% of reading
	Resolution	0.1 in. Hg.
Power Supply	100-120V, 1 Phase	50 / 60 Hz, 16A
	200-240V, 1 Phase	50 / 60 Hz, 16A
Weight		Net weight approximately 60kg
Dimensions (WxDxH)		18.9 x 24.7 x 44.3 inches
Data Logging		Up to 1000 measurements